















The offer of alu-clad DURWIN windows is addressed mainly to customers in the UK, Ireland and Scandinavian countries, where due to historical conditions outward opening windows are common.


Alu-clad windows combine positive features of wood that is naturally beautiful and perfect construction material and aluminum resistant to external conditions. Clever design and appropriate combination of these two different materials give excellent results.

DURWIN windows - nature inside and indestructible aluminum cladding outside. Alu-clad windows virtually require no maintenance and are an investment for future generations. They are perfect for buildings that are more exposed to weathering: mountain areas, coastal zones.



Durwin

Outward opening windows



TECHNICAL DATA

	Material	Engineered fingerjointed pine, selected pine, meranti, oak, other on request, laminated.		
Uw	Uw value	0.9 W/m²K (for test size window = 1230x1480 mm)		
	Glazing packages, Ug value	44mm (4-16-4-16-4), Ug = 0,6 W/m²K ; 24mm (4-16-4), Ug = 1,1 W/m²K Glass package may be modified.		
$\langle \cdot \rangle$	Air permeability	Class 4		
000	Watertightness	Class 3A		
<u>ဂျ</u> င	Wind load	Class C3		
4	Fittings	IPA, PN		
7	Surface treatment	Transparent colours based on current colour chart. Opaque colours based on RAL and NCS charts.		
	Aluminium claddings	Powder coated colours based on RAL chart (by Qualicoat sign, licence number: 1515).		

DIMENSIONAL RANGE

- Hingo typo	Min frame width	Max frame width	Min frame height	Max frame height	
Hinge type				Windows	French door
Side swing	476	976	393	1700	2450
Side hung	442	894	393	1700	2450

